


Config Table

SKU#	Power Cord Length	Plug/Power Cord
AP11101	-	-
AP11101	25mm <sup>2</sup> x3, 2M	-
AP11101-20P	25mm <sup>2</sup> x3, 2M	IEC320 C19 - IEC309 16A 3P6H IP44 Plug



IEC609 PLUG  
IP44 16A 3P6H

PUD Series: Basic  
 Input: 200-240V AC, 16A, 1Ph  
 Outlet: C13 [12]  
 CB/Bank: 1xBank  
 Outlet Color: Black/Red  
 Chassics Color: Black

THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF A-RACK AND SHALL NOT BE COPIED, REPRODUCED OR USED IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM A-RACK. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.

Drawn by	Description	Drawing No.	
Approved by	Basic PDU, 200-240V AC, 16A, 1Ph C13 [12]	AP11101	
	Version	Third Angle Projection	Unit: mm
	A1	A4	Sheet1 OF 1
Scale:	1:-		

Tolerance/Dimension  
 >120=400 ±0.5  
 >30=120 ±0.3  
 >6=30 ±0.2  
 >3=6 ±0.1  
 >0.5=3 ±0.1  
 16D  
 2768-M